

$$\mathsf{F}_{\nabla} = 2\pi \cdot \mathsf{r}^{3} \frac{\sqrt{\epsilon_{\mathsf{B}}}}{\mathsf{c}} \left(\frac{\epsilon - \epsilon_{\mathsf{B}}}{\epsilon + 2\epsilon_{\mathsf{B}}} \right) (\nabla \cdot \mathbf{I})$$

 F_{∇} = Optical force on particle towards higher intensity

r = Radius of particle


 ϵ_{B} = Dielectric constant of backround medium


 ε = Dielectric constant of particle

I = Light intensity (W/cm²)

∇ = Spatial derivative

FIG. 1











FIG. 4A










FIG. 9A






FIG. 9B











FIG. 12A












FIG. 22










FIG. 25

Before:

SCATTER FORCE SEPARATION






FIG. 26





HEMOGLOBIN - O 2 ABSORPTION SPECTRUM




FIG. 31




FIG. 32






FIG. 33



Before

FIG. 34

DISTRIBUTION OF ESCAPE VELOCITIES READING TAKEN IN PBS1% BSA BUFFER RAIN-X COATED SLIDE/CYTOP COATED COVERSLIP






FIG. 36

FIG. 37A

FIG. 37B

FIG. 37C


Laser beam

Phase1

Phase2



Phase3



Slow continuous movement

Quick stepping movement



WBC








FIG. 38



21/25



Sectioned sample field

FIG. 41




FIG. 42

Phase 1




FIG. 43A

Phase 2




FIG. 43B

Phase 3




FIG. 43C